

Oil Machinery Connector





Technical Data

Operating Temperature	Lower limit-55°C; Upper limit+125°C	Salty Spray Corrosion	>96 hours
Relative Humidity	At 40°C, reaching 95%, 21 days	Overvoltage Category	III
Vibration	Vibration frequency 10-100Hz, acceleration 2g	Degree of Pollution	2/3
Shock	Acceleration 30g/18ms	Mechanical Life	>500 Cycles

Insulation Resistance

Normal	High Temperature	Damp Heat
≥ 5000MΩ	≥ 1000MΩ	≥ 100MΩ





Material





Shell	Aluminum Alloy
Insert	Flame resistance UL94V-0
Contacts	Copper Alloy Silver plating does not require code labeling, while gold plating requires adding a "J" after the product code.

Shell Spec——Contacts Arrangement

View from mating face of pin contacts (P)

 $\phi 1.5$ $\phi 2.5$ $\phi 3.5$

Shell Spec	HFB 48			
Contacts No.	5	9	16	17
Contacts Arrangement				
Diameter Of Contacts × Qty	$\phi 3.5$ (50A) X5	$\phi 3.5$ (50A) X4 $\phi 2.5$ (25A) X5	$\phi 2.5$ (25A) X16	$\phi 1.5$ (10A) X17
Rated Voltage(V)	500	500	400	400
Withstand Voltage(V)	4000	4000	3000	4000

Shell Spec	HFB 48			
Contacts No.	22	24	26	31
Contacts Arrangement				
Diameter Of Contacts × Qty	$\phi 2.5$ (25A) X4 $\phi 1.5$ (10A) X18	$\phi 2.5$ (25A) X9 $\phi 1.5$ (10A) X15	$\phi 2.5$ (25A) X4 $\phi 1.5$ (10A) X22	$\phi 1.5$ (10A) X31
Rated Voltage(V)	400	400	400	400
Withstand Voltage(V)	2500	2500	2500	2500



SHANGHAI HUALUN INSTRUMENTS & ELECTRONICS CO., LTD.

SALES & MARKETING DEPARTMENT

ADD: Rm3409, Tower2, Kerry Everbright City, West
Tianmu Rd218, Shanghai

P.C. : 200070

TEL : 86-21-63178300 ext. 205

FAX : 86-21-63178083

E-MAIL : liz@hualunconnector.com

WEB : www.hualunconnector.com

FACTORY & HEADQUARTERS

ADD: Factory building 1 & 3, Jinjiang Industrial
Park, Qianyang Rd271, Shanghai

P.C. : 200333

- Hualun reserves the right to modify the technical and upgrade of the product
- Any form of diversion of this cataloge must be authorized by Hualun