



Receptacle TMS3100



Receptacle TMS3101



Receptacle TMS3102



Plug TMS3106



Plug TMS3108

TMS

MIL-DTL-5015

- Coupling: Thread
- Terminal: Solder



Index

Assemble Parts	2
Profile, Technical Data	3
Part Number Explanation	4-18
Receptacle① (Panel Mounted, No Protective Enclosure)	4
Receptacle② (Protective Enclosure, Clamp/Gland)	5
Receptacle③ (Free)	6
Receptacle④ (Adapter)	7
Plug	8
Shell Size-Arrangement No.	9-18
Angular Displacement of Insert	19
Size of Receptacle & Plug	20-28
Receptacle① (Panel Mounted, No Protective Enclosure)	20
Receptacle② (Protective Enclosure, Clamp/Gland)	21-22
Receptacle Mounting & Mounting Hole	23
Receptacle③ (Free)	24
Receptacle④ (Adapter)	25
Plug	26-28
Cap	29
Mounting Plate & Gasket	30



High-tech Enterprise Certificate



Foreign Invested Advanced




Enterprise Credit Rating AAA



Software Copyright



ISO9001, ISO14001, ISO45001



UL for YD series

Live parts should not be disassembled without authorization!!!





TIPS

- 1 After the wire is welded, be sure to seal the heat shrinkable sleeve at the welding site



- 2 Especially Recommended Assembly Nut Plate

The Feature of Assembly Nut Plate
Convenient and Fast! Firm!



Profile

- ◆ Design according to MIL5015, interchangeable with equivalent products.
- ◆ Insert: Halogen free & fire resistance thermoplastic UL94V-0; 2-60 pins. More than 65 types.
- ◆ Shell size-arrangement: 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40.
- ◆ Coupling: thread
- ◆ Terminal: solder
- ◆ Tools: hand crimp tool-M22520/1-01. Pneumatic crimp tool would be update efficiency and fit for mass crimping.
- ◆ Shell Protection degree: IP65/67
- ◆ Shock vibration: Class 1B (GB/T21563-2018 Shock and vibration test of rail transit locomotive and rolling stock equipment)
- ◆ Technical data qualified to NFF61030 (Normes francaises) & GB/T34119-2017 (Railway rolling stock-Electrical connectors) .
- ◆ Shell color: Black, Army Green
- ◆ TUV certification.

Hualun connectors are appointed by Chinese rail transport, engineering machinery, power electric power, thermoplastic machinery, industrial automation, and robot manufacturing enterprises. as a perennial supporting product.

Technical Data

Environmental

Operating Temperature	Upper limit+125°C * Lower limit-55°C
Relative Humidity	40°C±2°C 93%~95%
Salty Spray Corrosion	≥96hours
Protection Degree	IP65,IP67 (when mated,wired and mounted according to DS)
Shock Vibration	Class 1B (GB/T21563-2018 / IEC61373: 2010)

Note: * The upper limit temperature is the maximum internal hot spot temperature that occurs in either combination of electrical load and environmental conditions.

Contact current De-rating

Qty of contacts	1~10	11~20	21~30	31~50	51~80
Drop rate%	0	10	20	30	40

Mechanical Features

Type of contacts#	● 16#	⊕ 12#	⊗ 8#	⊙ 4#
retention force (min)	44.5N	66.7N	89.0N	89.0N
Minimum separation force	0.56N	0.83N	1.39N	2.78N

The contact crimp is sufficient to match the tensile strength of the cable

Type of contacts#	Wire Gauge		OD of Cable	
	AWG	mm ²	min	max
● 16#	20	0.50	1.63	3.30
	18	0.80		
	16	1.25		
⊕ 12#	14	2.00	2.90	4.32
	12	3.15		
⊗ 8#	10	6.30	4.17	6.48
	8	8.00		
⊙ 4#	6	12.50	6.91	9.40
	4	25.00		

Mechanical Life ≥500


Testing Condition

Temperature: 15°C~35°C	Relative Humidity: 20%~80%	Atmospheric Pressure: 73KPa~106KPa
------------------------	----------------------------	------------------------------------

Electric Features

Service rating	Inst.	A	D	E
Rated Voltage	250VDC	700VDC	1250VDC	1750VDC
	200VAC	500VAC	900VAC	1250VAC
Dielectric Withstand Voltage	1000VAC	2000VAC	2800VAC	3500VAC
Mechanical Spacing	-	1.59mm	3.18mm	4.76mm
Creepage Distance	1.59mm	3.18mm	4.76mm	6.35mm
Insulation Resistance	Normal: >5000MΩ, (Dynamic values see tableA)			
Type of contacts#	● 16#	⊕ 12#	⊗ 8#	⊙ 4#
Working Current	13A	23A	46A	80A
Contact Resistance	2.5mΩ	1.3mΩ	0.7mΩ	0.35mΩ

TableA The limit value of insulation resistance varies with temperature



Material of Main Parts

Shell	Material	Aluminum Alloy
	Finish	Electrophoretic Paint; Zinc Passivation
Insert	Material	Halogen free & fire resistance thermoplastic material
	Flame Retardant Grade	UL94V-0
Contacts	Material	Copper Alloy
	Plating	Silver; Gold
Grommet & Bushing	Low Fire Hazard Rubber	

Part Number (Explanation)

Receptacle ①

(Panel Mounted)
(No Protective Enclosure)

e.g. **1** **TMS** **31** **02** **S18-19** **N**

e.g. **2** **TMS** **31** **22** **P18-19** **W** **L**

1
 2
 3
 4
 5
 6

Explanation

1 TMS : Coupling (thread)

2 31 : Terminal (solder)

3 02 : Front Mounting
22 : Rear Mounting

} panel mounted,
 No protective enclosure

4 Insert:

S (P) 18 - 19

S: Socket Shell-size Arrangement No.
 P: Pin

Insert P/N: See [Page 9-18](#)

5 Insert Orientation:

N: Cardinal Points; (Default)


W, X, Y, Z, See [Page 19](#)

6 Shell Color:

◆ **H**: Black

◆ **L**: Army Green

■ Shell Size See [Page 20](#)



Part Number (Explanation)

Receptacle ② (Protective Enclosure)
(Clamp/Gland)

e.g. ①	TMS	31	20	S18-19	N	18A	
e.g. ②	TMS	31	00	P18-19	Y	18A	L
	①	②	③	④	⑤	⑥	⑦

Explanation

① **TMS** : Coupling (thread)

② **31** : Terminal (solder)

③ **00** : Front Mounting
20 : Rear Mounting

Protective Enclosure,
Clamp/Gland

④ Insert:

S(P) 18 - 19

S: Socket
P: Pin

Shell-size Arrangement No.

Insert P/N: See Page 9-18

⑤ Insert Orientation:

N: Cardinal Points; (Default)

W, X, Y, Z, See Page 19

⑥ Outlet Type:

◆ ****A** : Cable Clamp (3057+3420)
size

◆ **PG**** : PG Nylon Cable Gland Outlet
size

⑦ Shell Color:

◆ **H**: Black

◆ **L**: Army Green

■ Shell Size See
Page 21~23



Part Number (Explanation)

Receptacle ③

(Free)

e.g. **1** TMS 31 01 S18-19 N 18A

e.g. **2** TMS 31 01 P18-19 Y PG13.5 L

①

②

③

④

⑤

⑥

⑦

■ Shell Size See Page 24

Explanation

① **TMS** : Coupling (thread)

② **31** : Terminal (solder)

③ **01** : Free Receptacle

④ Insert:

S(P) 18 - 19

S: Socket
P: Pin

Shell-size Arrangement No.

Insert P/N: See Page 9-18

⑤ Insert Orientation:

N: Cardinal Points; (Default)

W, X, Y, Z, See Page 19

⑥ Outlet Type:

◆ ****A**_{size} : Cable Clamp (3057+3420)

◆ **PG****_{size} : PG Nylon Cable Gland Outlet

⑦ Shell Color:

◆ **H**: Black

◆ **L**: Army Green



Part Number (Explanation)

Receptacle ④ (Adapter)

e.g. ① TMS ② 31 ③ 022 S18-19P ⑤ N

e.g. ① TMS ② 31 ③ 011 ④ P18-19S ⑤ W ⑥ L

Explanation

① **TMS** : Coupling (thread)

② **31** : Terminal (solder)

③ **022** : Adapter (Square flange)

011 : Adapter (Round flange)

④ Insert:

S 18 - 19 P

S: Socket Shell-size Arrangement P: Pin
P: Pin No. S: Socket

Insert P/N: See [Page 9-18](#)

⑤ Insert Orientation:

N: Cardinal Points; (Default)

W, X, Y, Z, See [Page 19](#)

⑥ Shell Color:

◆ **H**: Black

◆ **L**: Army Green

■ Shell Size See [Page 25](#)



Part Number (Explanation)

Plug

e.g. **1** TMS 31 06 P18-19 N 18A

e.g. **2** TMS 31 08 S18-19 Y PG13.5 L

1
 2
 3
 4
 5
 6
 7

Explanation

1 TMS : Coupling (thread)

2 31 : Terminal (solder)

3 06 : Straight
08 : 90° Angled

{ Protective Enclosure,
 Clamp/Gland

4 Insert:

S (P) 18 - 19

S: Socket
 P: Pin Shell-size Arrangement No.

Insert P/N: See [Page 9-18](#)

5 Insert Orientation:

N: Cardinal Points; (Default)

W, X, Y, Z, See [Page 19](#)

6 Outlet Type:

◆ ****A** : Cable Clamp (3057+3420)
size

◆ **PG**** : PG Nylon Cable Gland
size

◆ **G**** : G Nylon Hose Clamp
size

7 Shell Color:

◆ **H**: Black

◆ **L**: Army Green

■ Shell Size See [Page 26~28](#)



Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12#

Type	14S							
P Shell Size- S Arrangement No.	P14S-2	S14S-2	P14S-5	S14S-5	P14S-6	S14S-6	P14S-7	S14S-7
Contact Arrangement	 4 Contact	 5 Contact	 6 Contact	 3 Contact				
Contact Size×Contact Qty.	16# × 4		16# × 5		16# × 6		16# × 3	
Service Rating	Inst.		Inst.		Inst.		A	

Type	14S		16S					
P Shell Size- S Arrangement No.	P14S-9	S14S-9	P16S-1	S16S-1	P16S-4	S16S-4	P16S-5	S16S-5
Contact Arrangement	 2 Contact	 7 Contact	 2 Contact	 3 Contact				
Contact Size×Contact Qty.	16# × 2		16# × 7		16# × 2		16# × 3	
Service Rating	A		A		D		A	

Type	16				18	
P Shell Size- S Arrangement No.	P16-9	S16-9	P16-10	S16-10	P18-1	S18-1
Contact Arrangement	 4 Contact	 3 Contact	 10 Contact			
Contact Size×Contact Qty.	16# × 2	12# × 2	12# × 3		16# × 10	
Service Rating	A		A		B.C.F.G = A Other = Inst.	

Type	18					
P Shell Size- S Arrangement No.	P18-3	S18-3	P18-10	S18-10	P18-11	S18-11
Contact Arrangement	 2 Contact	 4 Contact	 5 Contact			
Contact Size×Contact Qty.	12# × 2		12# × 4		12# × 5	
Service Rating	D		A		A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12#

Type	18					
P Shell Size- S Arrangement No.	P18-12	S18-12	P18-19	S18-19	P18-20	S18-20
Contact Arrangement						
Contact Size×Contact Qty.	16# × 6		16# × 10		16# × 5	
Service Rating	A		A		A	

Type	18		20			
P Shell Size- S Arrangement No.	P18-22	S18-22	P20-3	S20-3	P20-4	S20-4
Contact Arrangement						
Contact Size×Contact Qty.	16# × 3		12# × 3		12# × 4	
Service Rating	D		D		D	

Type	20					
P Shell Size- S Arrangement No.	P20-7	S20-7	P20-15	S20-15	P20-16	S20-16
Contact Arrangement						
Contact Size×Contact Qty.	16# × 8		12# × 7		16# × 7	12# × 2
Service Rating	C.D.E.F = A A.B.G.H = D		A		A	

Type	20					
P Shell Size- S Arrangement No.	P20-18	S20-18	P20-27	S20-27	P20-29	S20-29
Contact Arrangement						
Contact Size×Contact Qty.	16# × 6	12# × 3	16# × 14		16# × 17	
Service Rating	A		A		A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12# ⊗ 8#

Type	20		22	
P Shell Size- S Arrangement No.	P20-33	S20-33	P22-2	S22-2
Contact Arrangement	<p>Pin P</p> <p>11 Contact</p>	<p>S Socket</p> <p>11 Contact</p>	<p>Pin P</p> <p>3 Contact</p>	<p>S Socket</p> <p>3 Contact</p>
Contact Size×Contact Qty.	16# × 11		8# × 3	
Service Rating	A		D	

Type	22			
P Shell Size- S Arrangement No.	P22-5	S22-5	P22-8	S22-8
Contact Arrangement	<p>Pin P</p> <p>6 Contact</p>	<p>S Socket</p> <p>6 Contact</p>	<p>Pin P</p> <p>2 Contact</p>	<p>S Socket</p> <p>2 Contact</p>
Contact Size×Contact Qty.	16# × 4	12# × 2	12# × 2	
Service Rating	D		E	

Type	22			
P Shell Size- S Arrangement No.	P22-10	S22-10	P22-14	S22-14
Contact Arrangement	<p>Pin P</p> <p>4 Contact</p>	<p>S Socket</p> <p>4 Contact</p>	<p>Pin P</p> <p>19 Contact</p>	<p>S Socket</p> <p>19 Contact</p>
Contact Size×Contact Qty.	16# × 4		16# × 19	
Service Rating	E		A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12# ⊙ 8#

Type	22			
P Shell Size- S Arrangement No.	P22-18	S22-18	P22-19	S22-19
Contact Arrangement	Pin P 8 Contact	S Socket 8 Contact	Pin P 14 Contact	S Socket 14 Contact
Contact Size×Contact Qty.	16# × 8		16# × 14	
Service Rating	C,D,E = A Other = D		A	

Type	22			
P Shell Size- S Arrangement No.	P22-20	S22-20	P22-22	S22-22
Contact Arrangement	Pin P 9 Contact	S Socket 9 Contact	Pin P 4 Contact	S Socket 4 Contact
Contact Size×Contact Qty.	16# × 9		8# × 4	
Service Rating	A		A	

Type	22			
P Shell Size- S Arrangement No.	P22-23	S22-23	P22-28	S22-28
Contact Arrangement	Pin P 8 Contact	S Socket 8 Contact	Pin P 7 Contact	S Socket 7 Contact
Contact Size×Contact Qty.	12# × 8		12# × 7	
Service Rating	H = D Other = A		A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12# ⊗ 8#

Type	24			
P Shell Size- S Arrangement No.	P24-2	S24-2	P24-5	S24-5
Contact Arrangement	<p>Pin P</p> <p>7 Contact</p>	<p>S Socket</p> <p>7 Contact</p>	<p>Pin P</p> <p>16 Contact</p>	<p>S Socket</p> <p>16 Contact</p>
Contact Size×Contact Qty.	12# × 7		16# × 16	
Service Rating	D		A	

Type	24			
P Shell Size- S Arrangement No.	P24-7	S24-7	P24-10	S24-10
Contact Arrangement	<p>Pin P</p> <p>16 Contact</p>	<p>S Socket</p> <p>2 Contact</p>	<p>Pin P</p> <p>7 Contact</p>	<p>S Socket</p> <p>7 Contact</p>
Contact Size×Contact Qty.	16# × 14	12# × 2	8# × 7	
Service Rating	A		A	

Type	24			
P Shell Size- S Arrangement No.	P24-11	S24-11	P24-20	S24-20
Contact Arrangement	<p>Pin P</p> <p>9 Contact</p>	<p>S Socket</p> <p>3 Contact</p>	<p>Pin P</p> <p>11 Contact</p>	<p>S Socket</p> <p>2 Contact</p>
Contact Size×Contact Qty.	12# × 6	8# × 3	16# × 9	12# × 2
Service Rating	A		D	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12# ⊙ 8# ⊕ 4#

Type	24			
P Shell Size- S Arrangement No.	P24-22	S24-22	P24-28	S24-28
Contact Arrangement	<p>Pin P</p> <p>4 Contact</p>	<p>S Socket</p> <p>4 Contact</p>	<p>Pin P</p> <p>24 Contact</p>	<p>S Socket</p> <p>24 Contact</p>
Contact Size×Contact Qty.	8# × 4		16# × 24	
Service Rating	D		Inst.	

Type	28			
P Shell Size- S Arrangement No.	P28-10	S28-10	P28-11	S28-11
Contact Arrangement	<p>Pin P</p> <p>7 Contact</p>	<p>S Socket</p> <p>7 Contact</p>	<p>Pin P</p> <p>22 Contact</p>	<p>S Socket</p> <p>22 Contact</p>
Contact Size×Contact Qty.	12# × 3	8# × 2	16# × 18	12# × 4
Service Rating	G = D	Other = A	A	

Type	28			
P Shell Size- S Arrangement No.	P28-12	S28-12	P28-15	S28-15
Contact Arrangement	<p>Pin P</p> <p>26 Contact</p>	<p>S Socket</p> <p>26 Contact</p>	<p>Pin P</p> <p>35 Contact</p>	<p>S Socket</p> <p>35 Contact</p>
Contact Size×Contact Qty.	16# × 26		16# × 35	
Service Rating	A		A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12# ⊕ 4#

Type	28			
P Shell Size- S Arrangement No.	P28-16	S28-16	P28-20	S28-20
Contact Arrangement	<p>Pin P</p> <p>20 Contact</p>	<p>S Socket</p> <p>20 Contact</p>	<p>Pin P</p> <p>14 Contact</p>	<p>S Socket</p> <p>14 Contact</p>
Contact Size×Contact Qty.	16# × 20		16# × 4 12# × 10	
Service Rating	A			

Type	28			
P Shell Size- S Arrangement No.	P28-21	S28-21	P28-22	S28-22
Contact Arrangement	<p>Pin P</p> <p>37 Contact</p>	<p>S Socket</p> <p>37 Contact</p>	<p>Pin P</p> <p>6 Contact</p>	<p>S Socket</p> <p>6 Contact</p>
Contact Size×Contact Qty.	16# × 37		16# × 3 4# × 3	
Service Rating	A		D	

Type	28		32	
P Shell Size- S Arrangement No.	P28-A9	S28-A9	P32-7	S32-7
Contact Arrangement	<p>Pin P</p> <p>9 Contact</p>	<p>S Socket</p> <p>9 Contact</p>	<p>Pin P</p> <p>35 Contact</p>	<p>S Socket</p> <p>35 Contact</p>
Contact Size×Contact Qty.	16# × 5 4# × 4		16# × 28 12# × 7	
Service Rating	A		A.B.h.j = Inst. Other = A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12# ⊕ 4#

Type	32			
P Shell Size- S Arrangement No.	P32-13	S32-13	P32-17	S32-17
Contact Arrangement	<p>Pin P</p> <p>23 Contact</p>	<p>S Socket</p> <p>23 Contact</p>	<p>Pin P</p> <p>4 Contact</p>	<p>S Socket</p> <p>4 Contact</p>
Contact Size×Contact Qty.	16# × 18	12# × 5	4# × 4	4# × 4
Service Rating	D		D	

Type	32			
P Shell Size- S Arrangement No.	P32-22	S32-22	P32-73	S32-73
Contact Arrangement	<p>Pin P</p> <p>54 Contact</p>	<p>S Socket</p> <p>54 Contact</p>	<p>Pin P</p> <p>46 Contact</p>	<p>S Socket</p> <p>46 Contact</p>
Contact Size×Contact Qty.	16# × 54		16# × 46	
Service Rating	A		A	

Type	36	
P Shell Size- S Arrangement No.	P36-7	S36-7
Contact Arrangement	<p>Pin P</p> <p>47 Contact</p>	<p>S Socket</p> <p>47 Contact</p>
Contact Size×Contact Qty.	16# × 40	12# × 7
Service Rating	A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12#

Type	36	
P Shell Size- S Arrangement No.	P36-A22	S36-A22
Contact Arrangement	<p>Pin P</p> <p>22Contact</p>	<p>S Socket</p> <p>22Contact</p>
Contact Size×Contact Qty.	12# × 22	
Service Rating	D	

Type	36	
P Shell Size- S Arrangement No.	P36-52	S36-52
Contact Arrangement	<p>Pin P</p> <p>52Contact</p>	<p>S Socket</p> <p>52Contact</p>
Contact Size×Contact Qty.	16# × 52	
Service Rating	A	

Shell Size - Arrangement No.

View from mating face

● 16# ⊕ 12#


Type	40	
P Shell Size- S Arrangement No.	P40-1	S40-1
Contact Arrangement	<p style="text-align: center;">Pin P</p>	<p style="text-align: center;">S Socket</p>
Contact Size×Contact Qty.	16# × 24	12# × 6
Service Rating	D	

Type	40	
P Shell Size- S Arrangement No.	P40-A60	S40-A60
Contact Arrangement	<p style="text-align: center;">Pin P</p>	<p style="text-align: center;">S Socket</p>
Contact Size×Contact Qty.	16# × 60	
Service Rating	A	


Angular Displacement Of Insert

When more than two connectors with same Insert are applied to a device together, to alternate the inserts to different angulars can prevent mismatching.


Front face of pin insert



N: Angular Position



Key



Insert Code	Angular Displacement Of Insert				
	N	W	X	Y	Z
14S-2	0	—	120	240	—
14S-5	0	—	110	—	—
14S-6	0	—	—	—	—
14S-7	0	90	180	270	—
14S-9	0	70	145	215	290
16S-1	0	80	—	—	280
16S-4	0	35	110	250	325
16S-5	0	70	145	215	290
16-9	0	35	110	250	325
16-10	0	90	180	270	—
18-1	0	70	145	215	290
18-3	0	35	110	250	325
18-10	0	—	120	120	—
18-11	0	—	170	265	—
18-12	0	80	—	—	280
18-19	0	—	120	240	—
18-20	0	90	180	270	—
18-22	0	70	145	215	290
20-3	0	70	145	215	290
20-4	0	45	110	250	—
20-7	0	80	110	250	280
20-15	0	80	—	—	280
20-16	0	80	110	250	280
20-18	0	35	110	250	325
20-27	0	35	110	250	325
20-29	0	80	—	—	280
20-33	0	—	—	—	—
22-2	0	70	145	215	290
22-5	0	35	110	250	325
22-8	0	35	110	250	325
22-10	0	35	110	250	325
22-14	0	80	110	250	280
22-18	0	80	110	250	280
22-19	0	80	110	250	280
22-20	0	35	110	250	325
22-22	0	—	110	250	—
22-23	0	35	—	250	—
22-28	0	80	—	—	280
24-2	0	80	—	—	280
24-5	0	80	110	250	280
24-7	0	80	110	250	280
24-10	0	80	—	—	280
24-11	0	35	110	250	325
24-20	0	80	110	250	280
24-22	0	45	110	250	—
24-28	0	80	110	250	280
28-10	0	80	110	250	280
28-11	0	80	110	250	280
28-12	0	90	180	270	—
28-15	0	80	110	250	280
28-16	0	80	110	250	280
28-20	0	80	110	250	280
28-21	0	80	110	250	280
28-22	0	70	145	215	290
28-A9	0	110	250	260	280
32-7	0	80	125	235	280
32-13	0	80	110	250	280
32-17	0	45	110	250	—
32-22	0	80	110	250	280
32-73	0	36	—	—	—
36-7	0	80	110	250	280
36-A22	0	80	110	250	280
36-52	0	72	144	216	288
40-1	0	65	130	235	300
40-A60	0	80	110	250	280

Note: 32-22 has two angles of U (100) and V (260), besides N, W, X, Y and Z.



TUV SUD



ISO9001 ISO14001 ISO45001


Size of Receptacle

Receptacle ①

(Panel Mounted)
(No Protective Enclosure)

Front Mounting


TMS3102



Shell Spec	A Thread 2A	M $^{+0.2}_0$	L $_{\pm 0.3}$	K $_{\pm 0.2}$	$\varnothing N_{max}$	S $_{\pm 0.3}$	R $_{\pm 0.1}$	$\varnothing T_{\pm 0.1}^{+0.1}_0$	$\varnothing D1_{\pm 0.2}$
14S	7/8-20UNEF	14.2	25.7	3.2	19.2	30.0	23.0	3.2	20.0
16S	1-20UNEF				22.4	32.5	24.6		23.2
16		20.2	32.5	25.6	35.0	27.0	26.6		
18	1 1/8-18UNEF			29.0	38.0	29.4	30.0		
20	1 1/4-18UNEF	22.2	33.8	3.2	32.2	41.0	31.8	3.7	33.2
22	1 3/8-18UNEF				35.3	44.5	34.9		36.3
24	1 1/2-18UNEF	37.3	37.3	3.2	41.4	50.8	39.7	4.3	42.4
28	1 3/4-18UNS				47.8	57.0	44.5		48.8
32	2-18UNS	24.05	33.8	3.2	54.1	63.5	49.2	3.7	55.0
36	2 1/4-16UN				59.0	69.9	55.5		60.0
40	2 1/2-16UN								

Rear Mounting

TMS3122



Shell Spec	A Thread 2A	M $^{+0.2}_0$	L $_{\pm 0.3}$	K $_{\pm 0.2}$	$\varnothing N_{max}$	S $_{\pm 0.3}$	R $_{\pm 0.1}$	$\varnothing T_{\pm 0.1}^{+0.1}_0$	$\varnothing D2_{\pm 0.2}$
14S	7/8-20UNEF	18.2	24.7	3.2	19.2	30.0	23.0	3.2	26.0
16S	1-20UNEF				22.4	32.5	24.6		28.4
16		23.05	33.8	25.6	35.0	27.0	32.0		
18	1 1/8-18UNEF			29.0	38.0	29.4	35.5		
20	1 1/4-18UNEF	24.05	33.8	3.2	32.2	41.0	31.8	3.7	38.5
22	1 3/8-18UNEF				35.3	44.5	34.9		42.0
24	1 1/2-18UNEF	37.3	37.3	3.2	41.4	50.8	39.7	4.3	48.0
28	1 3/4-18UNS				47.8	57.0	44.5		55.0
32	2-18UNS	24.05	33.8	3.2	54.1	63.5	49.2	3.7	61.5
36	2 1/4-16UN				59.0	69.9	55.5		67.0
40	2 1/2-16UN								

Size of Receptacle


Receptacle ②

(Protective Enclosure)
(Clamp/Gland)

Front Mounting

TMS3100 Insulator **A

④ ⑤




Shell Spec	A Thread 2A	V Thread 2A	Cable Clamp (3057)+(3420)	OD of Cable(mm)	ØA _{max}	L	M ^{+0.2}	K _{±0.2}	S _{±0.3}	R _{±0.1}	ØT ^{+0.1} ₀
14S	7/8-20UNEF	3/4-20UNEF	14A	Ø 5-7	7.92	75~77	14.2	3.2	30.0	23.0	3.2
16S	1-20UNEF	7/8-20UNEF	16A	Ø 8-11	11.1				81~83	32.5	
16						35.0	27.0				
18	1 1/8-18UNEF	1-20UNEF	18A	Ø 11-14	14.3	83~85	20.2		38.0	29.4	
20	1 1/4-18UNEF	1 3/16-18UNEF	20A	Ø 14-16	16.2			86~88	41.0	31.8	
22	1 3/8-18UNEF					24A	Ø 16-19		19.1	44.5	34.9
24	1 1/2-18UNEF	1 7/16-18UNEF	24A	Ø 19-23	23.8	88~91	20.2	50.8	39.7	3.7	
28	1 3/4-18UNS							28A	Ø 24-31		31.7
32	2-18UNS	1 3/4-18UNS	32A	Ø 19-23	23.8	90~92	20.2	63.5	49.2	4.3	
36	2 1/4-16UN	2-18UNS	36A	Ø 24-31	31.7	90~92		69.9	55.5		
40	2 1/2-16UN	2 1/4-16UN	40A	Ø 31-34	35.0	103~105	20.2	69.9	55.5	4.3	

Front Mounting

TMS3100 Insulator PG**

④ ⑤



Shell Spec	A Thread 2A	PG Inner Thread	OD of Cable(mm)	ØN _{max}	L _{±0.3}	M ^{+0.2}	K _{±0.2}	H	S _{±0.3}	R _{±0.1}	ØT ^{+0.1} ₀
14S	7/8-20UNEF	PG9	Ø 4-8	19.2	52.7	14.2	3.2	22.0	30.0	23.0	3.2
16S	1-20UNEF	PG13.5	Ø 6-12	24.6				57.5	27.0	32.5	
16					28.0	35.0			27.0		
18	1 1/8-18UNEF	PG16	Ø 8.5-14	27.6	58.0	20.2		31.0	38.0	29.4	
20	1 1/4-18UNEF	PG21	Ø 12.5-18	33.6			33.0	41.0	31.8		
22	1 3/8-18UNEF	PG25	Ø 14-20	37.6	58.0	20.2	3.2	37.0	44.5	34.9	3.7
24	1 1/2-18UNEF							PG29	Ø 18-25	42.0	
28	1 3/4-18UNS	PG36	Ø 24-32	51.2	58.0	20.2	3.2	57.0	44.5	4.3	
32	2-18UNS							PG29	Ø 18-25		42.0
36	2 1/4-16UN	PG36	Ø 24-32	51.2	58.0	20.2	3.2	69.9	55.5	4.3	
40	2 1/2-16UN							PG36	Ø 24-32		51.2


Size of Receptacle

Receptacle ②

(Protective Enclosure)
(Clamp/Gland)

Rear Mounting


TMS3120 Insulator **A



Shell Spec	A Thread 2A	V Thread 2A	Cable Clamp (3057)+(3420)	OD of Cable(mm)	ØA _{max}	L	M ^{+0.2} ₀	K _{±0.2}	S _{±0.3}	R _{±0.1}	ØT ^{+0.1} ₀	
14S	7/8-20UNEF	3/4-20UNEF	14A	Ø 5-7	7.92	75~77	18.2	3.2	30.0	23.0	3.2	
16S	1-20UNEF	7/8-20UNEF	16A	Ø 8-11	11.1	81~83			23.05	32.5		24.6
18						11/8-18UNEF				1-20UNEF		18A
20	1 1/4-18UNEF	1 3/16-18UNEF	20A	Ø 14-16	16.2	86~88	24.05	3.7	38.0	29.4		
22	1 3/8-18UNEF								22A	41.0	31.8	
24	1 1/2-18UNEF	1 7/16-18UNEF	24A	Ø 16-19	19.1	88~91	24.05	4.3	44.5	34.9		
28	1 3/4-18UNS								28A	50.8	39.7	
32	2-18UNS	1 3/4-18UNS	32A	Ø 19-23	23.8	90~92	24.05	4.3	57.0	44.5		
36	2 1/4-16UN	2-18UNS	36A	Ø 24-31	31.7	90~92			63.5	49.2		
40	2 1/2-16UN	2 1/4-16UN	40A	Ø 31-34	35.0	103~105			69.9	55.5		


Rear Mounting

TMS3120 Insulator PG**



Shell Spec	A Thread 2A	PG Inner Thread	OD of Cable(mm)	ØN _{max}	L _{±0.3}	M ^{+0.2} ₀	K _{±0.2}	H	S _{±0.3}	R _{±0.1}	ØT ^{+0.1} ₀
14S	7/8-20UNEF	PG9	Ø 4-8	19.2	52.7	18.2	3.2	22.0	30.0	23.0	3.2
16S	1-20UNEF	PG13.5	Ø 6-12	24.6					57.5	23.05	
18					1 1/8-18UNEF	PG16	Ø 8.5-14	27.6			
20	1 1/4-18UNEF	PG21	Ø 12.5-18	33.6	58.0	24.05	33.0	38.0	29.4		
22	1 3/8-18UNEF							41.0	31.8		
24	1 1/2-18UNEF	PG25	Ø 14-20	37.6	24.05	48.0	37.0	44.5	34.9		
28	1 3/4-18UNS							50.8	39.7		
32	2-18UNS	PG29	Ø 18-25	42.0				57.0	44.5		
36	2 1/4-16UN	PG36	Ø 24-32	51.2				63.5	49.2		
40	2 1/2-16UN				69.9	55.5					

Receptacle Mounting & Mounting Hole



Shell Spec	$\varnothing T^{+0.1}_0$	$\varnothing D1_{\pm 0.2}$	$\varnothing D2_{\pm 0.2}$	$R_{\pm 0.1}$	L	Screw Spec
14S	3.2	20.0	26.0	23.0	33.0	M3 × 10
16S		23.2	28.4	24.6	34.4	
16		26.6	32.0	27.0	38.3	
18		30.0	35.5	29.4	41.7	
20		33.2	38.5	31.8	45.2	
22	3.7	36.3	42.0	34.9	48.7	M4 × 12
24		42.4	48.0	39.7	55.5	
28	4.3	48.8	55.0	44.5	62.4	
32		55.0	61.5	49.2	69.0	
36		60.0	67.0	55.5	75.0	
40						


Size of Receptacle

Receptacle ③

(Free)

Free TMS3101 Insulator **A


④ ⑤



Shell Spec	A Thread 2A	V Thread 2A	Cable Clamp (3057)+(3420)	OD of Cable(mm)	ØA max	C
14S	7/8-20UNEF	3/4-20UNEF	14A	Ø 5-7	7.92	25.2
16S	1-20UNEF	7/8-20UNEF	16A	Ø 8-11	11.1	28.8
16						
18	1 1/8-18UNEF	1-20UNEF	18A	Ø 11-14	14.3	31.5
20	1 1/4-18UNEF	1 3/16-18UNEF	20A	Ø 14-16	16.2	34.6
22	1 3/8-18UNEF		22A			38.0
24	1 1/2-18UNEF	1 7/16-18UNEF	24A	Ø 16-19	19.1	41.5
28	1 3/4-18UNS		28A			47.0
32	2-18UNS	1 3/4-18UNS	32A	Ø 19-23	23.8	53.7
36	2 1/4-16UN	2-18UNS	36A	Ø 24-31	31.7	60.2
40	2 1/2-16UN	2 1/4-16UN	40A	Ø 31-34	35.0	66.2

Free TMS3101 Insulator PG**

④ ⑤




Shell Spec	A Thread 2A	PG Inner Thread	OD of Cable(mm)	ØN max	H	C
14S	7/8-20UNEF	PG9	Ø 4-8	19.2	22.0	25.2
16S	1-20UNEF	PG13.5	Ø 6-12	24.6	27.0	28.8
16						
18	1 1/8-18UNEF	PG16	Ø 8.5-14	27.6	28.0	31.5
20	1 1/4-18UNEF	PG21	Ø 12.5-18	33.6	31.0	34.6
22	1 3/8-18UNEF					38.0
24	1 1/2-18UNEF	PG25	Ø 14-20	37.6	33.0	41.5
28	1 3/4-18UNS					47.0
32	2-18UNS	PG29	Ø 18-25	42.0	37.0	53.7
36	2 1/4-16UN	PG36	Ø 24-32	51.2	48.0	60.2
40	2 1/2-16UN					66.2

Size of Receptacle


Receptacle ④ (Adapter)

Adapter TMS31022 (Square flange)



Shell Spec	A Thread 2A	L1 ±0.7	K1 ±0.2	M +0.2 0	S ±0.3	R ±0.1	ØT +0.1 0	ØD2 ±0.2
14S	7/8-20UNEF	37.5	3.2	14.20	30.0	23.0	3.2	26.0
16S	1-20UNEF				32.5	24.6		28.4
16					35.0	27.0		32.0
18	1 1/8-18UNEF	51.4	4.0	19.0	38.0	29.4	3.7	35.5
20	1 1/4-18UNEF				41.0	31.8		38.5
22	1 3/8-18UNEF				44.5	34.9		42.0
24	1 1/2-18UNEF				50.8	39.7		48.0
28	1 3/4-18UNS	22.2			57.0	44.5	4.3	55.0
32	2-18UNS				63.5	49.2		61.5
36	2 1/4-16UN				69.9	55.5		67.0
40	2 1/2-16UN							

Adapter TMS31011 (Round flange)




Shell Spec	A Thread 2A	L2 ±0.7	K2 ±0.2	M +0.2 0		
14S	7/8-20UNEF	39.4	11.0	14.20		
16S	1-20UNEF				49.0	19.0
16						
18	1 1/8-18UNEF	52.2		20.6		
20	1 1/4-18UNEF					
22	1 3/8-18UNEF					
24	1 1/2-18UNEF					
28	1 3/4-18UNS	55.4		22.2		
32	2-18UNS					
36	2 1/4-16UN					
40	2 1/2-16UN					

Size of Plug


Plug

TMS3106 Insulator ****A** (Cable Clamp)



Shell Spec	A Thread 2B	V Thread 2A	Cable Clamp (3057) + (3420)	OD of Cable(mm)	ØA max	L1 max	L2 max
14S	7/8-20UNEF	3/4-20UNEF	14A	Ø 5-7	7.92	82	115
16S	1-20UNEF	7/8-20UNEF	16A	Ø 8-11	11.1	87	118
18						11/8-18UNEF	
20	1 1/4-18UNEF	1 3/16-18UNEF	20A	Ø 14-16	16.2	89	121
22	1 3/8-18UNEF		22A			92	
24	1 1/2-18UNEF	1 7/16-18UNEF	24A	Ø 16-19	19.1	95	124
28	1 3/4-18UNS		28A				
32	2-18UNS	1 3/4-18UNS	32A	Ø 19-23	23.8	96	127
36	2 1/4-16UN	2-18UNS	36A	Ø 24-31	31.7	100	
40	2 1/2-16UN	2 1/4-16UN	40A	Ø 31-34	35.0	112	

TMS3108 Insulator ****A** (Cable Clamp)



Shell Spec	A Thread 2B	V Thread 2A	Cable Clamp (3057) + (3420)	OD of Cable(mm)	ØA max	E max	F max	L max
14S	7/8-20UNEF	3/4-20UNEF	14A	Ø 5-7	7.92	40.0	47.0	70.0
16S	1-20UNEF	7/8-20UNEF	16A	Ø 8-11	11.1	40.8	59.5	72.5
18								
20	1 1/4-18UNEF	1 3/16-18UNEF	20A	Ø 14-16	16.2	42.6	61.8	79.0
22	1 3/8-18UNEF		22A					
24	1 1/2-18UNEF	1 7/16-18UNEF	24A	Ø 16-19	19.1	54.6	68.4	89.5
28	1 3/4-18UNS		28A					
32	2-18UNS	1 3/4-18UNS	32A	Ø 19-23	23.8	58.5	72.9	98.6
36	2 1/4-16UN	2-18UNS	36A	Ø 24-31	31.7	62.0	73.9	102.0
40	2 1/2-16UN	2 1/4-16UN	40A	Ø 31-34	35.0	79.0	76.9	108.7

Size of Plug


Plug

TMS3106 Insulator **PG**** (Nylon Cable Gland)

4 5




IP67



Shell Spec	A Thread 2B	PG Inner Thread	OD of Cable(mm)	L	H
14S	7/8-20UNEF	PG9	∅ 4-8	50	22.0
16S	1-20UNEF	PG13.5	∅ 6-12		60
16					
18	1 1/8-18UNEF	PG16	∅ 8.5-14	60	28.0
20	1 1/4-18UNEF	PG21	∅ 12.5-18		65
22	1 3/8-18UNEF				
24	1 1/2-18UNEF	PG25	∅ 14-20	65	33.0
28	1 3/4-18UNS				
32	2-18UNS	PG29	∅ 18-25	80	37.0
36	2 1/4-16UN	PG36	∅ 24-32		80
40	2 1/2-16UN				

TMS3106 Insulator **G**** (Nylon Hose Clamp)

4 5




Shell Spec	A Thread 2B	PG Inner Thread	OD of Cable(mm)	L	Nylon Hose Clamp Code
14S	7/8-20UNEF	PG9	∅ 4-8	50	G9
16S	1-20UNEF	PG13.5	∅ 6-12		60
16					
18	1 1/8-18UNEF	PG16	∅ 8.5-14	60	G16
20	1 1/4-18UNEF	PG21	∅ 12.5-18		65
22	1 3/8-18UNEF				
24	1 1/2-18UNEF	PG25	∅ 14-20	65	G25
28	1 3/4-18UNS				
32	2-18UNS	PG29	∅ 18-25	80	G29
36	2 1/4-16UN	PG36	∅ 24-32		80
40	2 1/2-16UN				

Size of Plug


Plug

TMS3108 Insulator **PG**** (Nylon Cable Gland)



Shell Spec	A Thread 2B	L1±0.2	L2±0.2	V Thread 2A	PG Inner Thread	OD of Cable(mm)	H
14S	7/8-20UNEF	47	30	3/4-20UNEF	PG9	∅ 4-8	22.0
16S	1-20UNEF	48		7/8-20UNEF	PG13.5	∅ 6-12	27.0
16		57					
18	1 1/8-18UNEF	58	35	1-20UNEF	PG16	∅ 8.5-14	28.0
20	1 1/4-18UNEF	61		1 3/16-18UNEF	PG21	∅ 12.5-18	31.0
22	1 3/8-18UNEF						
24	1 1/2-18UNEF	66	40	1 7/16-18UNEF	PG25	∅ 14-20	33.0
28	1 3/4-18UNS						
32	2-18UNS	72	45	1 3/4-18UNS	PG29	∅ 18-25	37.0
36	2 1/4-16UN	75	50	2-18UNS	PG36	∅ 24-32	48.0
40	2 1/2-16UN	78	55	2 1/4-16UN			

TMS3108 Insulator **G**** (Nylon Hose Clamp)




Shell Spec	A Thread 2B	L1±0.2	L2±0.2	V Thread 2A	PG Inner Thread	OD of Cable(mm)	Nylon Hose Clamp Code
14S	7/8-20UNEF	47	30	3/4-20UNEF	PG9	∅ 4-8	G9
16S	1-20UNEF	48		7/8-20UNEF	PG13.5	∅ 6-12	G13.5
16		57					
18	1 1/8-18UNEF	58	35	1-20UNEF	PG16	∅ 8.5-14	G16
20	1 1/4-18UNEF	61		1 3/16-18UNEF	PG21	∅ 12.5-18	G21
22	1 3/8-18UNEF						
24	1 1/2-18UNEF	66	40	1 7/16-18UNEF	PG25	∅ 14-20	G25
28	1 3/4-18UNS						
32	2-18UNS	72	45	1 3/4-18UNS	PG29	∅ 18-25	G29
36	2 1/4-16UN	75	50	2-18UNS	PG36	∅ 24-32	G36
40	2 1/2-16UN	78	55	2 1/4-16UN			

Protection Cap-Parts To Be Ordered Separately

Plug
Protection Cap



Size of Cap



Unit: mm


Dust Cap Code	Application
TMS25042-14	Shell 14 Plug
TMS25042-16	Shell 16 Plug
TMS25042-18	Shell 18 Plug
TMS25042-20	Shell 20 Plug
TMS25042-22	Shell 22 Plug
TMS25042-24	Shell 24 Plug
TMS25042-28	Shell 28 Plug
TMS25042-32	Shell 32 Plug
TMS25042-36	Shell 36 Plug
TMS25042-40	Shell 40 Plug

Shell Spec	D1 Max	D2 +0.6 -0	L1 Max	L2 Max
14S	27.5	4.3	100	29
16S	30.0			
16	33.5		115	37
18	37.0			
20	40.0			
22	43.5			
24	49.5	4.7	130	37
28	56.0			
32	62.5		190	37
36	73.5			
40	73.5	5.5	190	37

Receptacle
Protection Cap



Size of Cap



Unit: mm


Dust Cap Code	Application
TMS25043-14	Shell 14 Receptacle
TMS25043-16	Shell 16 Receptacle
TMS25043-18	Shell 18 Receptacle
TMS25043-20	Shell 20 Receptacle
TMS25043-22	Shell 22 Receptacle
TMS25043-24	Shell 24 Receptacle
TMS25043-28	Shell 28 Receptacle
TMS25043-32	Shell 32 Receptacle
TMS25043-36	Shell 36 Receptacle
TMS25043-40	Shell 40 Receptacle

Shell Spec	D1 Max	D2 +0.6 -0	L1 Max	L2 Max
14S	30.5	4.3	90	20
16S	33.0			
16	37.5		100	25
18	41.0			
20	44.0			
22	47.5			
24	54.5	5.5	115	25
28	61.0			
32	67.5		160	25
36	73.5			
40	73.5	5.5	160	25


Mounting Plate & Gasket

Rubber Sealing Gasket Size

● Rear Mounting






● Front Mounting



Shell Size	Rear Mounting ØD1	$R_{\pm 0.1}$	$S_{\pm 0.3}$	$\phi d_{+0.1}^0$	Front Mounting ØD2
14S	24.9	23.0	28.6	3.5	22.1
16S、16	28.2	24.6	32.5		25.3
18	30.9	27.0	35.0		28.4
20	34.3	29.4	38.0		31.6
22	37.7	31.8	41.3		34.8
24	41.2	34.9	44.5	3.7	38
28	46.8	39.7	50.8		44.3
32	53.4	44.5	57.2	4.5	50.7
36	59.6	49.2	63.5		57
40	65.5	55.5	69.9		61.9

Mounting Plate(Metal) Order Code, Size



Mounting Plate & Gasket

Code	Shell Size	$R_{\pm 0.1}$	$S_{\pm 0.3}$	ϕD	E	H	$\phi d_{+0.1}^0$	Thread M	Screw Spec
SG14	14S	23.0	30.0	24.9	15.8	2.6	6.3	M3	M3x10
SG16	16S、16	24.6	32.3	28.2	17.9				
SG18	18	27.0	34.6	30.9	20.2				
SG20	20	29.4	38.5	34.3	22.5				
SG22	22	31.8	40.8	37.7	23.5				
SG24	24	34.9	44.8	41.2	25.9				
SG28	28	39.7	51.2	46.8	29.1	3.0	8.0	M4	M4x12
SG32	32	44.5	59.1	53.4	30.7				
SG36	36	49.2	63.9	59.6	35.5				
SG40	40	55.5	74.7	65.5	38.6				



SHANGHAI HUALUN INSTRUMENTS & ELECTRONICS CO., LTD.

SALES & MARKETING DEPARTMENT

ADD: Rm3409, Tower2, Kerry Everbright City, West
Tianmu Rd218, Shanghai

P.C. : 200070

TEL : 86-21-63178300 ext. 205

FAX : 86-21-63178083

E-MAIL : liz@hualunconnector.com

WEB : www.hualunconnector.com

FACTORY & HEADQUARTERS

ADD: Factory building 1 & 3, Jinjiang Industrial
Park, Qianyang Rd271, Shanghai

P.C. : 200333

- Hualun reserves the right to modify the technical and upgrade of the product
- Any form of diversion of this cataloge must be authorized by Hualun